

2008 WERS Certified Products Directory - NFRC



www.wers.net

NOTES

1. U_w is the whole window *U-value*
2. $SHGC_w$ is the whole window *solar heat gain coefficient*
3. T_{vw} is the whole window *visible (light) transmittance*
4. Percentage improvement figures are compared with using base-case Generic Window 1 (3mm clear in standard aluminium frame)
5. A negative percentage improvement figure indicates performance worse than the base-case window
6. A positive percentage improvement figure indicates performance better than the base-case window
7. Maximum air infiltration is 5.0L/s.m² at a positive pressure difference of 75 Pa as measured according to AS 2047
8. Static performance (U_w $SHGC_w$ T_{vw} T_{dw}) calculated using Window 5.2 and Therm 5.2 software (LBNL), 2000-2003
9. Annual energy performance (stars and % improvements) calculated using Nationwide House Energy Rating Software (AccuRate) according to procedures of WERS 2008.
10. Results disclosed at National Fenestration Rating Council (NFRC) regulations.

07-May-08

Cedar & Baltic Windows				%	%	Total Window System Values - NFRC			
Window ID	Glazing	Cooling Stars	Heating Stars			Uw	SHGCw	Tvw	Air Inf.
WERS Generic Standard Industry Typical Timber Window - Single Glazed									
WER_03_002	3Clr	★	★★★	21%	24%	5.5	0.69	0.72	5
WER_03_005	6.38CP	★★★★☆	★★★☆☆	52%	33%	3.7	0.41	0.47	5
WER_03_016	5Gn	★★	★★★☆☆	38%	16%	5.4	0.50	0.39	5
WER_03_018	5EG	★★★☆☆	★★★☆☆	40%	15%	5.4	0.47	0.59	5
WERS Generic Standard Industry Typical Timber Window - Double Glazed									
WER_03_008	3/6/3	★★★☆☆	★★★★★☆☆	38%	47%	3.3	0.61	0.65	5
WER_03_011	3/12/3	★★★☆☆	★★★★★☆☆	40%	51%	3.0	0.61	0.65	5
WER_03_014	3/12/4	★★★★	★★★★★☆☆	48%	59%	2.1	0.58	0.59	5
WER_03_021	5Gn/6/5	★★★★☆	★★★★★☆☆	55%	37%	3.3	0.41	0.34	5

Glazing ID	Glazing Description
3Clr	3mm Clear
5EG	5mm EverGreen
5Gn	5mm Green
6.38CP	6.38mm ComfortPlus Neutral
3/6/3	3mm Clear / 6mm Air Gap / 3mm Clear
3/12/3	3mm Clear/12mm Air Gap/3mm Clear
3/12/4	3mm Clear / 12mm Air Gap / 4mm Clear
5Gn/6/5	5mm Green/6mm Air Gap/5mm Clear
5EG/12Ar/4LE	5mm EverGreen / 12mm Argon Gap / 4mm Low-E
6EG/10Ar/4LE	6mm EverGreen / 10mm Argon / 4mm Low-E