

2008 WERS Certified Products Directory - NFRC



www.wers.net

NOTES

1. U_w is the whole window *U-value*
2. $SHGC_w$ is the whole window *solar heat gain coefficient*
3. T_{vw} is the whole window *visible (light) transmittance*
4. Percentage improvement figures are compared with using base-case Generic Window 1 (3mm clear in standard aluminium frame)
5. A negative percentage improvement figure indicates performance worse than the base-case window
6. A positive percentage improvement figure indicates performance better than the base-case window
7. Maximum air infiltration is 5.0L/s.m² at a positive pressure difference of 75 Pa as measured according to AS 2047
8. Static performance (U_w $SHGC_w$ T_{vw} T_{dw}) calculated using Window 5.2 and Therm 5.2 software (LBNL), 2000-2003
9. Annual energy performance (stars and % improvements) calculated using Nationwide House Energy Rating Software (AccuRate) according to procedures of WERS 2008.
10. Results disclosed at National Fenestration Rating Council (NFRC) regulations.

07-May-08

Euroaluminium Australia				%	%	Total Window System Values - NFRC			
Window ID	Glazing	Cooling Stars	Heating Stars			Uw	SHGCw	Tvw	Air Inf.
WERS Generic Standard Industry Typical Aluminium Window - Single Glazed									
WER_03_001	3Clr			0%	-5%	7.7	0.78	0.75	5
WER_03_003	6.38LE	★★	★★	37%	11%	5.8	0.48	0.49	5
WER_03_015	5Toned	★		21%	-13%	7.7	0.57	0.41	5
WER_03_017	5SuperToned	★☆		24%	-15%	7.7	0.53	0.62	5
WERS Generic Standard Industry Typical Aluminium Window - Double Glazed									
WER_03_006	3/6/3	★	★★★	21%	26%	5.4	0.69	0.68	5
WER_03_009	3/12/3	★	★★★★☆	22%	31%	5.0	0.69	0.68	5
WER_03_012	3/12/4LE	★☆	★★★★	31%	41%	4.0	0.65	0.62	5
WER_03_019	5SuperToned/6/5	★★☆	★★★	40%	16%	5.3	0.47	0.36	5

Glazing ID	Glazing Description
3Clr	3mm Clear
5EG	5mm EverGreen
5Gn	5mm Green
6.38CP	6.38mm ComfortPlus Neutral
3/6/3	3mm Clear / 6mm Air Gap / 3mm Clear
3/12/3	3mm Clear/12mm Air Gap/3mm Clear
3/12/4	3mm Clear / 12mm Air Gap / 4mm Clear
5Gn/6/5	5mm Green/6mm Air Gap/5mm Clear
5EG/12Ar/4LE	5mm EverGreen / 12mm Argon Gap / 4mm Low-E
6EG/10Ar/4LE	6mm EverGreen / 10mm Argon / 4mm Low-E